FEATURES

1)Resolution HD 1024P
2)16mm lens
3)Support Onvif, POE
4)Support P2P (Plug to play)
5)Night vision 50M
6) 1 year Warranty
7) With CE,FCC, RoHS certificates

SPECS

ΜΊΤΞΛΜ

Model	MVT-M7424
Sensor type	Hi3518C+SONY IMX238,1/3" Sony sensor
Compress standard	H.264 Main profile,MPEG4,MJPEG
Main Stream	PAL 1024P@25fps
Shutter speed	1/50(1/60) ~ 1/100,000 s
Video compression	32Kbps~16Mbps
Lens	3M Pixels 16mm Lens
Lens Interface type	(CS)
Day and night switch system	IR-CUT
Audio Compression	ADPCM
Minimum illumination	0.05Lux @Color,0.01Lux B/W
Image setting	Saturation, brightness, contrast ratio can be adjusted by CMS and IE browser
Intelligent alarm	Motion detecting, video loss, network cable disconnection, and IP address conflict
Memory Function	Network storage
Network Protocol	P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP
General function	Flash-prevention, double stream, heartbeat, password protection
Communication interface	1ch RJ45,10M/100M ethernet ports adaptively
LED	4pcs led array

MTEAM

IR distance	100m
IP Grade	



FACTORY & OFFICE

MTEAM



EXHIBITIONS

ΜΥΤΞΛΜ

