

● FEATURES



- 1) outdoor IP66, mini 4" speed dome camera, Pan continuously 360° rotate, tilt 90°, rotation with auto-flip, Horizontal Speed $\square 0.1^\circ \square 300^\circ/s \square$, Vertical Speed $\square 0.1^\circ \square 180^\circ/s \square$
- 2) Built-in 10X automatic integrated moduel, more convenient and flexible operation
- 3) 128 presets, 4 tour, 4 scan, 4 patterns, clock function 8 programmable zones with editable title, preset precision degree 0.01°
- 4) Real time, temperature display , Low temperature protected function
- 5) Support privacy masking zone ,3D-NR
- 6) Lightningproof design, provide subtle Lightning Protection
- 7) 1/3 inch, sony 222 CMOS 2MP/1080P 10x Optical Zoom ICR

● SPECS



PTZ Specs	
Manual speed	Pan $\square 0.2^\circ \square 300^\circ/s \square$
	Tilt $\square 0.2^\circ \square 180^\circ/s \square$
Power supply	DC 12V
Rotation	Pan continuously 360°, tilt 0 $\square 90^\circ$ with auto-flip
Speed Proportion	As the length of focus, to auto-adjust the speed
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Scan	355°programmable, 4 scan
Pattern	4 patterns, and each record time is not less than 180s
Tour	4 tour, and speed & park time of presets can be set.
Remote controlling	RS485
Baud rate (RS485)	2400 $\square 4800 \square 9600/19200$ bps
ID range	1-254
Power consumption	6W

Temperature	-10°C□+50°C/ -40°C□+60°C via heater & Fans (Optional)
Installation	Wall installation, ceiling installation
Net weight	1.8Kg
CAM Specs	
Sensor	1/3" Sony 322 CMOS Sensor+SONY4191 ISP 1920*1080
OPTICS	Optical x10,Zoom f = 5.1mm ~ 51mm
Angle	Appr. 55.2°(Wide) to 3.2°(Tele)
Min. Illumination	Color : 0.5 lux , BW : 0.1lux
S/N (Y signal)	52dB
White Balance	Auto
ICR	Manual/Auto
DNR	Auto / Off / Low / Middle / High
HLC	Off / On
Max Gain	Auto
IRIS	Auto
FLIP	Vertical , Horizontal ,Vertical-Horizontal,OFF Selectable

● PRODUCT PICTURE

M' TEAM



● FACTORY & OFFICE

M'TEAM



● EXHIBITIONS

M'TEAM

