

## ● FEATURES



- 1.Support P2P function; Easily monitoring via PC, iPhone and Andriod mobile phone.(Mobile phone APP:Qmeye)
- 2.Support remotely playback the recorded video in NVR by PC and mobile phone
- 3.The same Client Software can manage different type security cameras .
- 4.Support Software update, Support 20 Languages
- 5-Support ONVIF

## ● SPECS



Model Number:MVT-N6516

Resolution: 16\*(720P/960P/1080P)

Channel:16CH

Video Output:HDMI/VGA

Audio:16CH

Alarm:4ch input, 1ch output

Recording Resolution:16\*960P/1080P

Playback (realtime):16\*960P or 8\*1080P

HDD: Support 2pc sata hdd up to 8TB

Mobile phone monitor:support Iphone,Android,Blackberry,Windows,Symbian

ONVIF:Support

P2P:Support

Chipeset:3535

Digial Zoom:Support

Size: 380(L)\*300(W)\*55(H)mm

Model	□	MVT-N6516
Operation	□	Embedded Linux
Image edit control	□	Image edit adjustable,both changable and fix stream optional
Double stream	□	Can be set up in each channel
Video standard	□	1080P(1920×1080)30FPS/S/960P/(1280×960)/720P(1280×720)30FPS/S frames /second
Monitor image quality	□	1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)
Image dynamic detection	□	Multiple detection areas can be installed level 6 sensitivity(IPC)
Image playback quality	□	4ch 1080P real time/8ch 720P/960P real time synchronous playback
Video mode	□	Support manual, automatic, dynamic monitoring, alarm trigger video mode (need) IPC support part
Backup mode	□	U disk, USB mobile hard disk, USB burn, network storage and backup
Operate mode	□	Mouse
login locally	□	admin and password

Save recording	<input type="checkbox"/>	local hard disk and network
External interface	Video input	1080P(1920×1080)IP camera
<input type="checkbox"/>	Video output	1ch VGA+1ch HDMI +1TV
<input type="checkbox"/>	Audio output	1ch RCA audio output
<input type="checkbox"/>	Network interface	1ch RJ45,10M/100M ethernet ports adaptively
<input type="checkbox"/>	USB connect port	2 x USB connect port
<input type="checkbox"/>	Wireless interface	Support external USB and 3G equipment
<input type="checkbox"/>	RS485	RS485*1
<input type="checkbox"/>	Alarm input	4ch
<input type="checkbox"/>	Alarm output	1ch
Hard disk	HDD port	2 SATA HDD port
<input type="checkbox"/>	Maximum capacity	Maximum 3TB each SATA
Cell phone monitoring	<input type="checkbox"/>	iOS Android
Power	<input type="checkbox"/>	12V/4A
Working temperature	<input type="checkbox"/>	-10°C~55°C
Working humidity	<input type="checkbox"/>	10~90%
NVR size	<input type="checkbox"/>	380mm×295mm×55mm
Weight	<input type="checkbox"/>	2.7KG(without HDD)

## ● PRODUCT PICTURE

M' TEAM





**M TEAM**

### **P2P Function Advantages:**

**\*No stable IP address needed**

**\*No DDNS setup needed**

\*No Router setup needed

\*Reducing your after-sales cost

## ● P2P FUNCTION



### Mobile Phone View

(All MVTEAM DVR, AHD DVR, CVI DVR, SDI DVR, NVR support)



### Achieve Monitoring All kinds of Cameras in One Screen on Computer



## ● FACTORY & OFFICE

M TEAM



## ● EXHIBITIONS

M TEAM



For more about AHD Products welcome to Visit [FAQ](#)