2MP Outdoor Hybrid AHD TVI CVI Analog 4.2" Mini PTZ Camera

FEATURES

*Solution:NVP2441H+IMX323,1080P
*5.1-51mm 10X zoom lens,ICR
*4.2" Outdoor Mini PTZ Camera
*Without IR leds
*Day/Night(ICR)
*0.1°-200 °pan speed & 0.1°- 180°/s tilt speed,90°tilt auto flip
*128 presets,4 auto scans,4 tours,4 patterns
*Clock function
*With OSD menu,AHD UTC/RS485 remote controlling
*Pelco-P/D (Auto recognition)
* lightning-proof, surge-proof, IP66
*Working Temperature: -20℃ □ +60℃
*DC12V/1.5A power supply

SPECS

PTZ Specs	
Manual speed	Pan□0.2°□300°/s□
	Tilt□0.2°□180°/s□
Power supply	DC 12V/1.5A
Rotation	Pan continuously 360°, tilt 0□90° with auto-flip
Speed Proportion	As the length of focus, to auto-adjust the speed
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Scan	355°programmable, 4 scan
Pattern	4 patterns, and each record time is not less than 180s
Tour	4 tour, and speed & park time of presets can be set.
Romote controlling	RS485
Baud rate (RS485)	2400□4800□9600/19200 bps
ID range	1-254
Power consumption	6W
Temperature	-10℃□+50℃/ -40℃□+60℃ via heater & Fans (Optional)
Installation	Wall installation, ceiling installation

Net weight	1.8Kg
CAM Specs	
Sensor	NVP2441H+IMX323
	1080P 1920*1080
OPTICS	Optical x10,Zoom f = 5.1mm ~ 51mm
Angle	Appr. 55.2°(Wide) to 3.2°(Tele)
Min. Illumination	Color : 0.5 lux , BW : 0.1lux
S/N (Y signal)	52dB
White Balance	Auto
ICR	Manual/Auto
DNR	Auto / Off / Low / Middle / High
HLC	Off / On
Max Gain	Auto
IRIS	Auto
FLIP	Vertical , Horizontal ,Vertical-Horizontal,OFF Selectable

PRODUCT PICTURE

FACTORY & OFFICE

EXHIBITIONS