360 Degree Hidden CCTV Camera Indoor VR Wifi Light Bulb Camera H100-E

FEATURES

ΜΥΤΞΛΜ

*Adopt CMOS image sensor, with high resolution 1.3MP, 2MP, 3MP for your option

*360 Degree wide view angle, no blind area, applicable to different scenarios, supporting 4 different viewing modes

*Support two-way audio, voice prompt.

*ICR infrared filter automatic switching, realize the real day and night monitoring

*Support the standard clear, HD resolution to watch,to adapt for variety of network environment *Support mobile phones real-time monitoring

*Support PTZ control, remote capture, audio and video recording

*Global network coverage, anytime, anywhere smooth Watch

*Support mobile APP N_eye 3C

Easy installation, Screw it easily

Led bulb shape, standard E27 base, AC 220V voltage.



Multi-Angle Monitor

Support multi-scene modes













SPLIT SCREENS



CORRIDER

Video footage storage

Support max 128GB micro TF card for recording.



Intergrated with LED illumination



Show Appearance



















Mobile Phone View



SPECS

j –	Model No.	H100-E6	H100-E8	H100-E9
Camera	Resolution	1.3MP	2.0MP	3.0MP
	Minimum illumination	0.02Lux @(F2.0,AGC ON) ,0 Lux with IR		
	Shutter	Shutter adaptation		
	Camera lens	360 degree fisheye lens		
	Lens interface type	M12		
	Day and night conversion	ICR infrared filter		
	Digital noise reduction	3D digital noise reduction		
Compression	Video compression standa	H.264		
	Coding type	H.264 Main Profile		
	Video compression rate	HD, SD, rate adaptation.		
	Audio compression standa	AAC		
	Audio compression rate	Rate adaptation		
	Frame rate	Max:25fps network transmission rate: adaptive adjustment		
	Image setting	Brightness, contrast, saturation, etc.		
		(through the client to adjust the setting)		
Network	Storage function	Support Micro SD card (max 128G)		
Function	Intelligent alarm	Video is lost, the network is disconnected, and the power is disconnected.		
	General functions	Reverse, capture, mobile alarm, password protection,		
		video playback, remote control, two-way intercom		
Wireless	Wireless standard	IEEE802.11b, 802.11g, 802.11n Draft		
Parameter	frequency range	2.4 GHz ~ 2.4835 GHz		
	Channel bandwidth	Support 20/40MHz		
	security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS		
	transmission speed	11b: 11Mbps,11g:54Mbps,11n:135Mbps		
General specification	temperature and humidity			
	Power	AC 110V~220V		
	Power consumption	3W MAX		
	Infrared radiation distance	MAX 5meter		
	Size(mm)	87mm x 87mm x 127mm		
	Weight	200g		



Shipping: Based on the your demands to choose the best shipping way.

Contact us:

If you have any question, welcome to Contact us.

Your close attention to our company is highly appreciated. Welcome to visit our official website **<u>www.mvteamcctv.com</u>**

Related Articles about Wifi IP Camera:

How to Set Motion Detection for Wifi IP Camera? How Long Video Records Does a TF Card Can Save for Wifi Cameras? How to remote view MVTEAM Wifi IP Camera on Computer?