

## Main Features:

- 1.0M/1.3M/2.0M pixel full real time optional,Highest resolution 1080P
- follow HD and CVBS video standard
- with 6-22mm(M12) vari-focal Lens
- Water Resistant Rate:IP66
- support transmission distance above 500M under general 75- 3 coaxial cable without loss
- High-speed, long-distance, real-time transmission
- support OSD menu
- with ICR switching , to achieve Day and Night monitoring
- Used genuinely imported 3rd generation IR LEDs and megapixel high definition lens, these cameras have been featured as great performance in color restoration,image definition and night viewing.

Model	MVT-AH11T
Sensor	1/3" CMOS(AR0130+NVP2431H ) 1.3M/1024P,with IR CUT
SIGNAL	PAL / NTCS
Video Output	HD-AHD/CVBS
Effective Pixels	1280(H)*1024(V)
Min. Illumination	0.05Lux @Color,0.01Lux B/W
Shutter	4/25s~1/45,000s
Video Frequency	1280×1024@50 fps;1280×1024@60 fps
Synchronization	Internal
Video Output	1-channel BNC HDAHD/CVBS high definition video output
BLC	optional
OSD	optional
AWB	Automatic / manual / day / night
Day/Night	Auto(ICR) / Color / B/W
Transmission Distance	Over 500m via 75-3 coaxial cable
Power Supply	DC 12V±10%
Working Environment	30°C~+60°C/Less than 95%RH(no condensation)

Power Consumption 4W MAX

## ● PRODUCT PICTURE

M TEAM



## ● FACTORY & OFFICE

M TEAM



