

Main Features:

- *1MP/1.3MP/2MP AHD Cameras available
- * AHD-CVI-TVI-CVBS 4-in-1 Camera available
- * OSD Menu optional(D-WDR ,BLC function etc)
- * Can be used as CVBS Camera with free switch Button
- * Transmit Over Coaxial Cable 500m
- * Support Balun transferring

Application Places:

Apply to replace the old analog system and new projects in the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

Model No.	Key Specifications	
MVT-AH11A	Gray and White color optional, with 6mm(M12) or 3.6mm Lens, 36pcs×d5 IR leds, 30m IR Distance, 3-Axis bracket with cable built-in	1/4" CMOS □OV9712+NVP2431H□ 1.0M/720P, with IR CUT
MVT-TAH11N		1/4" CMOS□AR0141+HDI8901□ 1.0M/720P, Low Illumination, with IR CUT, TVI-CVI-AHD-CVBS 4-in-1 Camera
MVT-AH11N		1/4" CMOS □AR0141+NVP2431H □ 1.0M/720P, Low Illumination, with IR CUT
MVT-AH11T		1/3" CMOS □AR0130+NVP2431H □ 1.3M/1024P, with IR CUT
MVT-AH11B		1/3" CMOS □SONY225+NVP2431H □ 1.3M/1024P, with IR CUT
MVT-AH11R		1/3" CMOS □AR0237+NVP2441H □ 2MP/1080P, with IR CUT
MVT-AH11P		1/3" CMOS □SONY322+NVP2441H □ 2MP/1080P, with IR CUT

Model	MVT-AH11P		
Sensor	1/3" CMOS(SONY322+NVP2441H)		
Resolution	2MP		
Effective Pixels	1920(H)*1080(V)		
Lens	3MP HD 3.6mm(M12)		
Leds	36pcs leds		
IR Distance	30m		
SIGNAL	PAL		
Video Output	HD-AHD		
Min. Illumination	0.01Lux F1.2		
Shutter	4/25s~1/45,000s		
Synchronization	Internal		
Video Output	1-channel BNC HDAHD high definition video output		
OSD	Optional	BLC	BLC/HLC/OFF
		D-WDR	OFF/ON(Level 0-8)/Auto
		3D-NR	OFF/LOW/MID/HIGH
		Day/Night	Auto, Color, B/W, Ext
		Defog	OFF/AUTO
Power Supply	DC 12V±10%		
Working Environment	-20°C~+50°C/Less than 95%RH(no condensation)		
Power Consumption	4W MAX		
IP Rank	IP66, outdoor use,Metal Case		

● PRODUCT PICTURE

M' TEAM



● FACTORY & OFFICE

M'TEAM



● EXHIBITIONS

M'TEAM

