

**Main Features:**

- \*1MP/1.3MP/2MP AHD Cameras available
- \* AHD-CVI-TVI-CVBS 4-in-1 Camera available
- \* OSD Menu optional( D-WDR ,BLC function etc)
- \* Can be used as CVBS Camera with free switch Button
- \* Transmit Over Coaxial Cable 500m
- \* Support Balun transferring

**Application Places:**

Apply to replace the old analog system and new projects in the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

Model	MVT-AH26A
Sensor	OV9712+NVP2431H
SIGNAL	PAL / NTCS
Video Output	HD-AHD/CVBS
Effective Pixels	1280(H)*720(V)
Min. Illumination	0.05Lux @Color,0.01Lux B/W
Shutter	4/25s~1/45,000s
Video Frequency	1280×1024@50 fps □ 1280×1024@60 fps
Synchronization	Internal
Video Output	1-channel BNC HDAHD/CVBS high definition video output
BLC	optional
OSD	optional
AWB	Automatic / manual / day / night
Day/Night	Auto(ICR) / Color / B/W
Transmission Distance	Over 500m via 75-3 coaxial cable
Power Supply	DC 12V±10%
Working Environment	30°C~+60°C/Less than 95%RH(no condensation)

Power Consumption	4W MAX
-------------------	--------

● PRODUCT PICTURE

M TEAM



Unit:mm



## ● FACTORY & OFFICE

M'TEAM



## ● EXHIBITIONS

M'TEAM

