

Main Features:

- 1.0M / 1.3M / 2.0M pixel full optional real-time, high definition 1080P
- The follow-HD and CVBS video standard
- Fixed lens 6mm (M12)
- Waterproof Rating: IP66
- 75- 3 general support under the coaxial cable transmission distance without loss of over 500M
- High-speed, long-distance, real-time transmission
- Support OSD
- IC transition, to reach day and night viewing
- 3rd generation actually imported used IR LEDs and high-resolution megapixel lens, this camera color restoration, image definition, and has been featured as a big performance night vision.

Applications:

Finance, supermarkets, telecommunications, government, schools, airports, factories, hotels, museums and other places to apply the high-resolution requirements.

| | | |
|-----------------------|---|--|
| Model | MVT-AH30A | MVT-AH30N |
| Sensor | 1/4" CMOS pixelplus 1.0M/ 720P OV9712 | 1/4" CMOS pixelplus 1.0M/ 720P AR0141 |
| SIGNAL | PAL / NTCS | |
| Video Output | HD-AHD/CVBS | |
| Effective Pixels | 1280(H)*720(V) | 1280(H)*720(V) |
| Min. Illumination | 0.01Lux F1.2 | |
| Shutter | 4/25s~1/45,000s | |
| Synchronization | Internal | |
| Video Output | 1-channel BNC HDAHD/CVBS high definition video output | |
| BLC | optional | |
| OSD | optional | |
| AWB | Automatic / manual / day / night | |
| Day/Night | Auto(ICR) / Color / B/W | |
| Transmission Distance | Over 500m via 75-3 coaxial cable | |
| Power Supply | DC 12V±10% | |
| Working Environment | 30°C~+60°C/Less than 95%RH(no condensation) | |

| | |
|-------------------|--------|
| Power Consumption | 4W MAX |
|-------------------|--------|

● PRODUCT PICTURE

M TEAM



● FACTORY & OFFICE

M TEAM



