

## ● FEATURES



- 1)Resolution HD 1024P
- 2)6mm lens (CS)
- 3)Support Onvif, POE
- 4)Support P2P (Plug to play)
- 5)Night vision 30M
- 6) 1 year Warranty
- 7) With CE,FCC, RoHS certificates

## ● SPECS



| Model                       | MVT-M2824C                                                                        |
|-----------------------------|-----------------------------------------------------------------------------------|
| Sensor type                 | Hi3518E+Aptina130,1/3" CMOS sensor                                                |
| Compress standard           | H.264 Main profile,MPEG4,MJPEG                                                    |
| Main Stream                 | 1280*1024@30fps                                                                   |
| Shutter speed               | 1/50(1/60) ~ 1/100,000 s                                                          |
| Video compression           | 32Kbps~16Mbps                                                                     |
| Lens                        | 3M Pixels 6mm Lens                                                                |
| Lens Interface type         | (CS)                                                                              |
| Day and night switch system | IR-CUT                                                                            |
| Audio Compression           | ADPCM                                                                             |
| Minimum illumination        | 0.05Lux @Color,0.01Lux B/W                                                        |
| Image setting               | Saturation,brightness,contrast ratio can be adjusted by CMS and IE browser        |
| Intelligent alarm           | Motion detecting, video loss,network cable disconnection, and IP address conflict |
| Memory Function             | Network storage                                                                   |
| Network Protocol            | P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP                            |
| General function            | Flash-prevention, double stream, heartbeat, password protection                   |
| Communication interface     | 1ch RJ45,10M/100M ethernet ports adaptively                                       |
| LED                         | 36pcs leds                                                                        |
| IR distance                 | 30m                                                                               |

IP Grade

IP66

## 1.3MP IP Camera

(Dome/Onvif/POE)



**M'TEAM**

### ● FACTORY & OFFICE

**M'TEAM**



