

## ● FEATURES



### **1080P,1/3" Ex-view 1.3 Mega Pixel CMOS,10X Optical Zoom ,53.2°-5.65° WIDE-TELE**

- 1) Indoor 4 inch Mini dome
- 2) IR range: 25-35m
- 3) Day/Night(ICR), auto iris , auto focus , AWB, AGC , BLC.
- 4) Pan range: 0°~360° Continue  
Tilt range: 0°~90° Flip  
Pan Speed: Max 300°/sec  
4 Pattern auto scan path  
8 group programmable scanning track
- 5) Surge & Wave protection 4 inch Mini dome

[IP PTZ Setting Video](#)

## ● SPECS



|                                                                                                                     |                                              |
|---------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| Pan continuously 360° rotate, tilt 90° rotation with auto-flip                                                      |                                              |
| Horizontal Speed 0.1°~220°/s, Vertical Speed 0.1°~180°/s                                                            |                                              |
| IR range more than 35 m, constant current control, synchronous switch                                               |                                              |
| Humanize focus and speed proportion                                                                                 |                                              |
| 128 presets (titles can be set);                                                                                    |                                              |
| Tour is based on presets, speed & park time of presets can be set.                                                  |                                              |
| support scanning between left limit and right limit at an appointed speed.                                          |                                              |
| Park action function, can auto-call presets or start-up tour, pattern and scan after dome idle for a period of time |                                              |
| Memory store function, built-in memorizer which can store parameters of camera & functions of PTZ.                  |                                              |
| Built-in TVS wave-proof.                                                                                            |                                              |
|                                                                                                                     |                                              |
| CAMERA SPEC                                                                                                         |                                              |
| Sensor                                                                                                              | 1/2.3", AR0130 1.3M Pixel CMOS               |
| Angle                                                                                                               | 68° / 6.7° (Wide-Tele)                       |
| Lens                                                                                                                | Focal length 5.1-51mm                        |
| Zoom                                                                                                                | 10x Optical Zoom                             |
| Min. Illumination                                                                                                   | 0.02LUX                                      |
| Iris                                                                                                                | Auto                                         |
| White Balance                                                                                                       | Auto/Manual/indoor/outdoor                   |
| IRcf Control                                                                                                        | Auto* / Manu (soft)                          |
| Focus Length                                                                                                        | ~1.0m(tele)~0.01m(wide)                      |
| Signal Process                                                                                                      | HIS3516C                                     |
| White Balance                                                                                                       | Auto* / Manu (R Gain/B Gain, Level: UP~DOWN) |
| IRcf Control                                                                                                        | Auto* / Manu (soft)                          |
|                                                                                                                     |                                              |
| Specification                                                                                                       |                                              |

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| DSP                | HIS3518A+AR0130                                         |
| IR range           | 35m                                                     |
| Ethernet           | 10Base -T, /100Base-TX, RJ45 Connector                  |
| Frame              | 25/30 fps                                               |
| Image compression  | H.264/MJPEG                                             |
| Dual stream        | Support                                                 |
| Onvif              | Onvif 2.4 Ver.                                          |
| Protocols          | TCP/IP.HTTP.DHCP.PPPoE.UDP.RTP/RTCP.DNS.DDNS .UPnP.SMTP |
| Manual speed       | Pan 0.2° 200°/s                                         |
|                    | Tilt 0.2° 100°/s                                        |
| Preset speed       | 200°/S                                                  |
| Rotation           | Continuously 360° tilt 0° 90° with auto-flip            |
| Speed Proportion   | Human-oriented focal length/speed adaptation            |
| Preset             | 128 preset, title can be edited                         |
| Auto-flip          | Tilt down 90°, with auto-flip 180°                      |
| Scan               | 355° programmable 1 scan                                |
| Pattern            | 1 patterns, time and speed can be set                   |
| OSD                | Built-in                                                |
| Privacy            | Support                                                 |
| Temperature        | -20°C +60°C                                             |
| Humidity           | 0 95% Non-condensation                                  |
| Protection grade   | IP66, lightning-proof, surge-proof                      |
| Power/ consumption | DC12V/ 24W(IR on)                                       |
| Net weight         | 2.5kg                                                   |

## ● PRODUCT PICTURE

M'TEAM



## ● FACTORY & OFFICE

M' TEAM



## ● EXHIBITIONS

M' TEAM

