

## 1080P,1/3" Ex-view 1.3 Mega Pixel CMOS,10X optical Zoom ,53.2°-5.65° WIDE-TELE

- 1) 4 inch Mini dome IR range:60-70m
- 2)Day/Night(ICR),auto iris ,auto focus ,AWB,AGC ,BLC.
- 3) Pan range: 0°~360° Continue  
Tilt range: 0°~90° Flip  
Pan Speed: Max 200°/sec
- 4) Preset: 128  
4 Pattern auto scan path  
8 group programmable scanning track
- 5) Surge & Wave protection
- 6) waterproof

[IP PTZ Setting Video](#)

|                                                                                                                     |                               |
|---------------------------------------------------------------------------------------------------------------------|-------------------------------|
| Pan continuously 360° rotate, tilt 90° rotation with auto-flip                                                      |                               |
| Horizontal Speed 0.1°~220°/s, Vertical Speed 0.1°~180°/s                                                            |                               |
| IR range more than 60 m, constant current control, synchronous switch                                               |                               |
| Humanize focus and speed proportion                                                                                 |                               |
| 128 presets (titles can be set);                                                                                    |                               |
| Tour is based on presets, speed & park time of presets can be set.                                                  |                               |
| support scanning between left limit and right limit at an appointed speed.                                          |                               |
| Park action function, can auto-call presets or start-up tour, pattern and scan after dome idle for a period of time |                               |
| Memory store function, built-in memorizer which can store parameters of camera & functions of PTZ.                  |                               |
| Built-in TVS wave-proof.                                                                                            |                               |
|                                                                                                                     |                               |
|                                                                                                                     |                               |
| CAMERA SPEC                                                                                                         |                               |
| Sensor                                                                                                              | 1/2.3",AR0130 1.3M Pixel CMOS |
| Angle                                                                                                               | 68°/ 6.7°(Wide-Tele)          |
| Lens                                                                                                                | Focal length 5.1-51mm         |
| Zoom                                                                                                                | 10x Optical Zoom              |
| Min. Illumination                                                                                                   | 0.02LUX                       |
| Iris                                                                                                                | Auto                          |
| White Balance                                                                                                       | Auto/Manual/indoor/outdoor    |

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
| IRcf Control          | Auto* / Manu (soft)                                     |
| Focus Length          | ~1.0m(tele)~0.01m(wide)                                 |
| Signal Process        | HIS3516C                                                |
| White Balance         | Auto* / Manu (R Gain/B Gain, Level: UP~DOWN)            |
| IRcf Control          | Auto* / Manu (soft)                                     |
|                       |                                                         |
| Specification         |                                                         |
| DSP                   | HIS3518A+AR0130                                         |
| IR range□             | 60m                                                     |
| Ethernet              | 10Base -T, /100Base-TX, RJ45 Connector                  |
| Frame                 | 25/30 fps                                               |
| Image compression     | H.264/MJPEG                                             |
| Dual stream           | Support                                                 |
| Onvif                 | Onvif 2.4 Ver.                                          |
| Protocols             | TCP/IP.HTTP.DHCP.PPPoE.UDP.RTP/RTCP.DNS.DDNS .UPnP.SMTP |
| Manual speed          | Pan□0.2°□200°/s□                                        |
|                       | Tilt□0.2°□100°/s□                                       |
| Preset speed          | 200°/S                                                  |
| Rotation              | Continuously 360°□tilt 0□90° with auto-flip             |
| Speed Proportion      | Human-oriented focal length/speed adaptation            |
| Preset                | 128 preset, title can be edited                         |
| Auto-flip             | Tilt down 90°, with auto-flip 180°                      |
| Scan                  | 355° programmable □1 scan                               |
| Pattern               | 1 patterns, time and speed can be set                   |
| OSD                   | Built-in                                                |
| Privacy               | Support                                                 |
| Temperature           | -20°C□+60°C                                             |
| Humidity              | 0□95%□Non-condensation□                                 |
| Protection grade      | IP66, lightning-proof, surge-proof                      |
| Power/<br>consumption | DC12V/ 24W(IR on)                                       |
| Net weight            | 2.5kg                                                   |

● PRODUCT PICTURE

M'TEAM



● FACTORY & OFFICE

M'TEAM



