

Features:

1. Cmos/CCD Sensor
- 2.Signal is uncompressed, transport via coaxial
- 3.Easy to be connected, plug and play
- 4.Low temperature protected function,suitable for different environment
- 5.Lightingproof design

Specification:

- Powerful 10x optical zoom
- High resolution@700TVL/600TVL
- WDR(DWDR),Day/Night(ICR),DNR(2D&3D) Auto iris,Auto focus,AWB,AGC,BLC
- Max300°/s pan speed,360°continuous pan rotation
- Up to 128 presets,4 auto scan,4 tour,4 pattern
- Power up Action,Idle Motion,Time Task support
- 1500V Wave&surge protection,Temperature:-10~50°C,DC12V

Model	MVT-M05
Manual speed	Pan 0.1°~300°/s
	Tilt 0.1°~180°/s
Power supply	DC 12V
Rotation	Pan 360°continuously, tilt 0°~90° with auto-flip
Speed Proportion	human-oriented focal length/ speed adaptation
Preset	128 preset, title can be edited
Auto-flip	Tilt 90°, with auto-flip 180°
Scan	355°programmable, 4 scan
Pattern	4 patterns, and each record time is not less than 180s
Tour	4 tour
RTC	Real clock function,can set auto function
Display zone	8 programmable zones with editable title

Temperature indicating	Low temperature protection function
Remote controlling	RS485
Baud rate (RS485)	2400□4800□9600/19200 bps
ID range	1-254
Power consumption	6W/9W(IR on)
Temperature	-10°C□+50°C
Installation	Wall mont,Pendant
Net weight	1.3Kg

PRODUCT PICTURE



● FACTORY & OFFICE

M TEAM



● EXHIBITIONS

M TEAM



For more about AHD Products welcome to Visit [FAQ](#)