

Main Features:

- 1.0M/1.3M/2.0M pixel full real time optional, Highest resolution 1080P
- follow HD and CVBS video standard
- 6mm(M12) fixed Lens
- Water Resistant Rate: IP66
- support transmission distance above 500M under general 75- 3 coaxial cable without loss
- High-speed, long-distance, real-time transmission
- support OSD menu
- with ICR switching , to achieve Day and Night monitoring
- Used genuinely imported 3rd generation IR LEDs and megapixel high definition lens, these cameras have been featured as great performance in color restoration, image definition and night viewing.

Application Places:

Apply to the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

| | | |
|-----------------------|---|--|
| Model | MVT-AH28A | MVT-AH28N |
| Sensor | 1/4" CMOS pixelplus 1.0M/ 720P OV9712 | 1/4" CMOS pixelplus 1.0M/ 720P AR0141 |
| SIGNAL | PAL / NTCS | |
| Video Output | HD-AHD/CVBS | |
| Effective Pixels | 1280(H)*720(V) | 1280(H)*720(V) |
| Min. Illumination | 0.01Lux F1.2 | |
| Shutter | 4/25s~1/45,000s | |
| Synchronization | Internal | |
| Video Output | 1-channel BNC HDAHD/CVBS high definition video output | |
| BLC | optional | |
| OSD | optional | |
| AWB | Automatic / manual / day / night | |
| Day/Night | Auto(ICR) / Color / B/W | |
| Transmission Distance | Over 500m via 75-3 coaxial cable | |

| | |
|---------------------|---|
| Power Supply | DC 12V±10% |
| Working Environment | 30°C~+60°C/Less than 95%RH(no condensation) |
| Power Consumption | 4W MAX |

● PRODUCT PICTURE

M TEAM



● FACTORY & OFFICE

M TEAM



