

Low illumination 1080P 2MP POE Outdoor Starlight IP Camera MVT-M1880S

Starlight IP Camera

Super Low-Light Effect (Under 0.001Lux)

★
STARLIGHT

🚶
MOTION

🖼️
1080P HD

P2P

POE



No light



B/W Mode

Low light



Color Mode

Daytime



Clear Color Mode

FEATURES

M TEAM

- *Adopts Hisilicon DSP Hi3516CV300 plus Sony CMOS IMX291, resolution upto 1080P/2MP
- *Super good performance in low light environment, low illumination under 0.001Lux
- *Compression format
- *3MP 2.8-12mm varifocal lens, 35m IR distance

Starlight IP camera VS Common Camera in low light environment.



If you want to view the real image quality of starlight ip camera, please check below video record.

Warmly notice: please do setup the player image quality to 1080p when watch the video.

MVTEAM Starlight IP Camera Clear Color Image at Dayti...



2017-12-13 11:09



MVTEAM Starlight IP Camera Video Record(No Light)



2017-12-13 00:13



Adopt infrared antireflection panel design, make the camera with better night vision.



Infrared Antireflection Panel

Quality reflective overlay, surface-emitting technology, can magnify the effect of focus, improve product performance and reliability.



HD 3MP 2.8-12mm vari-focal lens(M12 Mount),bring more clear image.



Adjustable Bracket



Size



IP66 Waterproof Grade,give you more reliable protection



● SPECS

M' TEAM

Model	MVT-M1880S
Sensor type	1/2.8" SONY CMOS IMX291(Low illumination)
DSP	Hi3516CV300
Compression format	H.264/JPEG/AVI/MJPEG
Resolution	1080P 1920*1080
Shutter speed	1/50(1/60) ~ 1/100,000 s
Video compression	32Kbps~16Mbps
Lens	Megapixel HD 2.8~12mm Lens(M12)
Lens Interface type	(M12)
Day and night switch system	IR-CUT
Audio Compression	ADPCM
WDR	Support DWDR
Minimum illumination	0.001Lux
Image setting	Saturation,brightness,contrast ratio can be adjusted by CMS and IE browser
Intelligent alarm	Motion detecting, video loss,network cable disconnection, and IP address conflict
Memory Function	Network storage
Network Protocol	P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP
General function	Flash-prevention, double stream, heartbeat, password protection
Communication interface	1ch RJ45,10M/100M ethernet ports adaptively
LED	42pcs IR leds

IR distance	35m
ONVIF	Support ONVIF 2.4
Power	DC 12V/1A Power adaptor or make POE on extension Video Cable
Operating Temperature	-10°C~50°C

▼ Packages



Brand Camera Package



Neutral Camera Package



Brand DVR Package



Package: MVTEAM Brand Box Or Netural Box Or Specified by customer.

▼ Shipping












Shipping: Based on the your demands to choose the best shipping way.

Contact us:

If you have any question, welcome to [Contact us](#).

Your close attention to our company is highly appreciated.

Welcome to visit our official website www.mvteamcctv.com to view video demos,download product catalog and read CCTV technical articles