

● FEATURES



- 1) outdoor IP66, mini 4.2" speed dome camera, Pan continuously 360° rotate, tilt 90°, rotation with auto-flip, Horizontal Speed $\square 0.1^{\circ} \square 300^{\circ}/s$, Vertical Speed $\square 0.1^{\circ} \square 180^{\circ}/s$
- 2) Built-in 10X automatic integrated module, more convenient and flexible operation
- 3) 128 presets, 4 tour, 4 scan, 4 patterns, clock function 8 programmable zones with editable title, preset precision degree 0.01°
- 4) Real time, temperature display, Low temperature protected function
- 5) Support privacy masking zone, 3D-NR
- 6) Lightningproof design, provide subtle Lightning Protection Indoor, IR range $\square 35$ to 40 m, constant current control, synchronous switch

● SPECS



Model No.	All-in-one Camera	Specification
MVT-MO502	1/3 inch, Sony Effio-E CCD 10x 700TVL, No ICR	- Indoor, IR range $\square 35$ to 40 m, constant current control, synchronous switch - indoor mini 4.2" speed dome camera, Pan continuously 360° rotate, tilt 90°, rotation with auto-flip, Horizontal Speed $\square 0.1^{\circ} \square 300^{\circ}/s$, Vertical Speed $\square 0.1^{\circ} \square 180^{\circ}/s$ - Built-in 10X automatic integrated module, more convenient and flexible operation 128 presets, 4 tour, 4 scan, 4 patterns, clock function 8 programmable zones with editable title, preset precision degree 0.01° - Real time, temperature display, Low temperature protected function - Support privacy masking zone, 3D-NR - Lightningproof design, provide subtle Lightning Protection
MVT-MO503	1/3 inch, CMOS 10x 600TVL, with ICR	
MVT-MO504	1/3", COMS 1099, 700TVL, 6MM lens	



