

- 1.Support P2P function; Easily monitoring via PC, iPhone and Andriod mobile phone.(Mobile phone APP:Qmeye)
- 2.Support remotely playback the recorded video in DVR by PC and mobile phone
- 3.The same Client Software can manage different type security cameras .
- 4.Support Software update, Support 20 Languages

Model	MVT-6308H	
<b>System</b>	<b>Compression</b>	H.264 Standard compression
	<b>Operation</b>	Embedded Linux
<b>Video</b>	<b>Input</b>	8XBNC,(1.0Vp-p,75Ω) D1
	<b>Output</b>	1BNC,(1.0Vp-p,75Ω),1VGA,HDMI 1080P
<b>Audio</b>	<b>Standard</b>	PAL 100F/S,PAL120F/S
	<b>Input</b>	2×RCA
<b>Display</b>	<b>Output</b>	1 ×RCA
	<b>Display Split</b>	1/4/8/
<b>Recording</b>	<b>Resolution</b>	1024*768 1280*1024 1280*720@60p 1920*1080@60p
	<b>Recording Priority</b>	Manual,timing,motion detection, video blind and video loss recording
<b>Network</b>	<b>Performance</b>	8CH D1 Real Time
	<b>Network function</b>	TCP/IP,UDP,DHCP,DNS,IP filter, PPPOE, E-mail, Alarm server, UPNP, DDNS,DNS Binding
<b>Alarm</b>	<b>Mobile monitoring</b>	Support Window Mobile, iPhone,iPad, Android, Blackberry,Symbian and 3G
	<b>Alarm input/output</b>	NO
<b>Playback &amp;Backup</b>	<b>Playback channel</b>	8CH
	<b>Playback performance</b>	8CH Real Time
<b>Data storage</b>	<b>Search mode</b>	Time/date, Motion detection
	<b>Backup mode</b>	U-disk/Hard disk/USB CD/DVD-RW/Download
<b>Hard disk</b>		1SATA,Maximum 4TB

<b>Auxiliary Interface</b>	<b>RS485</b>	PTZ control
	<b>Power supply</b>	12V/6A
	<b>Power consumption</b>	≤30W
<b>Environment</b>	<b>Working environment</b>	-10°C~+55°C/10~90%RH/86~106KPa
	<b>Dimension</b>	240*260*60mm(DVR size)
	<b>Weight</b>	3.0kg(Without HDD)

● PRODUCT PICTURE



**P2P Function Advantages:**

- \*No stable IP address needed**
- \*No DDNS setup needed**
- \*No Router setup needed**
- \*Reducing your after-sales cost**

## Mobile Phone View

(All MVTEAM DVR, AHD DVR, CVI DVR, SDI DVR, NVR support)



## Achieve Monitoring All kinds of Cameras in One Screen on Computer



## ● FACTORY & OFFICE

M TEAM



## ● EXHIBITIONS

M TEAM

