

Main Features:

- *1MP/1.3MP/2MP AHD Cameras available
- * AHD-CVI-TVI-CVBS 4-in-1 Camera available
- * OSD Menu optional(D-WDR ,BLC function etc)
- * Can be used as CVBS Camera with free switch Button
- * Transmit Over Coaxial Cable 500m
- * Support Balun transferring

Application Places:

Apply to replace the old analog system and new projects in the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

Model No.	Key Specifications	
MVT-AH21A	with 2.8-12mm(M12) vari-focal Lens,42pcs×Φ5 IR leds,35m IR Distance,bracket with cable built-in,Gray and White color optional	1/4" CMOS OV9712+NVP2431H 1.0M/720P,with IR CUT
MVT-TAH21N		1/4" CMOS AR0141+HDI8901 1.0M/720P,Low Illumination,with IR CUT, TVI-CVI-AHD-CVBS 4-in-1 Camera
MVT-AH21N		1/4" CMOS AR0141+NVP2431H 1.0M/720P,Low Illumination,with IR CUT
MVT-AH21T		1/3" CMOS AR0130+NVP2431H 1.3M/1024P,with IR CUT
MVT-AH21B		1/3" CMOS SONY225+NVP2431H 1.3M/1024P,with IR CUT
MVT-AH21R		1/3" CMOS AR0237+NVP2441H 2MP/1080P,with IR CUT
MVT-AH21P		1/3" CMOS SONY322+NVP2441H 2MP/1080P,with IR CUT

Model	MVT-AH21P
Sensor	1/3" CMOS(SONY322+NVP2441H)
Resolution	2MP
Effective Pixels	1920(H)*1080(V)
Lens	3MP HD 2.8-12mm(M12)
Leds	42pcs leds
IR Distance	35m
SIGNAL	PAL or NTSC

Video Output	HD-AHD		
Min. Illumination	0.01Lux F1.2		
Shutter	4/25s~1/45,000s		
Synchronization	Internal		
Video Output	1-channel BNC HDAHD high definition video output		
OSD	Optional	BLC	BLC/HLC/OFF
		D-WDR	OFF/ON(Level 0-8)/Auto
		3D-NR	OFF/LOW/MID/HIGH
		Day/Night	Auto, Color, B/W, Ext
		Defog	OFF/AUTO
Power Supply	DC 12V±10%		
Working Environment	-20°C~+50°C/Less than 95%RH(no condensation)		
Power Consumption	4W MAX		
IP Rank	IP66, outdoor use,Metal Case		

● PRODUCT PICTURE

M' TEAM



● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

