

Main Features:

- 1.0M/1.3M/2.0M pixel full real time optional, Highest resolution 1080P
- follow HD and CVBS video standard
- 6mm(M12) fixed Lens
- Water Resistant Rate: IP66
- support transmission distance above 500M under general 75-3 coaxial cable without loss
- High-speed, long-distance, real-time transmission
- support OSD menu
- with ICR switching, to achieve Day and Night monitoring
- Used genuinely imported 3rd generation IR LEDs and megapixel high definition lens, these cameras have been featured as great performance in color restoration, image definition and night viewing.

Application Places:

Apply to the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

Specs:

MVT-AH35A	IR Vandalproof Dome Cameras, with 3.6mm(M12) lens 12pcs×Φ5 IR leds 10m IR distance	1/4" CMOS OV9712+NVP2431H 1.0M, with IR CUT
MVT-TAH35N		1/4" CMOS AR0141+HDI8901 1.0M, TVI-CVI-AHD-CVBS 4-in-1 Camera
MVT-AH35N		1/4" CMOS AR0141+NVP2431H 1.0M, Low Illumination, with IR CUT
MVT-AH35T		1/3" CMOS AR0130+NVP2431H 1.3M, with IR CUT
MVT-AH35B		1/3" CMOS SONY225+NVP2431H 1.3M, with IR CUT
MVT-AH35R		1/3" CMOS AR0237+NVP2441H 2.0M, with IR CUT
MVT-AH35P		1/3" CMOS SONY322+NVP2441H 2.0M, with IR CUT

Pictures:



● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

