

FEATURES



1. Economical Security camera
2. Good image quality and cheap price
3. Widely compatible, able to match AHD DVR and All Standalone DVR
4. Easy to operate, Plug and Play
5. Advanced CMS software supporting 3G remote view

SPECS



| Model | MVT-R1141O | MVT-R1141Z |
|----------------------|--|--|
| Active Pixel | 976*496 | P: 976*582 |
| | | N: 976*494 |
| Resolution | 600TVL | 700TVL |
| Video Out | 1.0Vp-p Composite Signal (75ohm) | 1.0Vp-p Composite Signal (75ohm) |
| SYNC | Internal | Internal |
| Sensor | PC7030 | P: 3089 |
| | | |
| Minimum Illumination | 0.01Lux | 0.01Lux |
| Gama adjust | 0.45 | 0.45 |
| Electric Shutter | PAL:1/50s-1/100000s NTSC:1/60s-1/100000s | PAL:1/50s-1/100000s NTSC:1/60s-1/100000s |
| S/N Ratio | 48dB(min)(AGC closed) | 48dB(min) |
| DNR | - | |
| AWB | AUTO | |
| | | AUTO |
| | | |
| AGC | AUTO | AUTO |
| BLC | - | |
| OSD | - | |
| D-WDR | - | - |
| SWDR | - | - |
| | | - |
| | | - |
| HLC | - | - |
| D-Zoom | - | - |
| IR-Smart | - | - |
| Day/Night | - | - |
| Motion Detection | - | - |
| Language | - | - |
| Power | 50mA | 50mA |
| Dissipation | | |

| | | |
|-----------------------|---|---|
| Power Input | DC12V±1V | DC12V±1V |
| Operation Temperature | Temperature -10°C~+60°C, Humidity less than 85%RH | Temperature -10°C~+60°C, Humidity less than 85%RH |

● PRODUCT PICTURE

M' TEAM



New Appearance CCTV Cameras



MVT-R46
8mm(CS) Lens,
42 pcs IR leds



MVT-R30
8mm Lens,
42pcs×Φ5 IR leds



MVT-R21
2.8-12mm
vari-focal Lens,
42pcs×Φ5 IR leds



MVT-R62
2.8-12mm
vari-focal Lens,
42pcs×Φ5 IR leds



MVT-R58
9-22mm
vari-focal Lens,
72pcs×Φ5 IR leds



MVT-D30
6mm lens,
24pcs×Φ5 IR leds



MVT-D22
6mm lens,
36pcs×Φ5 IR leds



MVT-D28
6mm lens,
36pcs×Φ5 IR leds



MVT-D29
2.8-12mm
vari-focal Lens,
36pcs×Φ5 IR leds



MVT-D26
2.8-12mm(M12)
vari-focal Lens

● FACTORY & OFFICE

M TEAM



● EXHIBITIONS

M TEAM



For more about AHD Products welcome to Visit [FAQ](#)