Plug and Play Two-way intercom P/T 1080P 2MP Wifi Smart Cloud IP Camera

*Adopt 1/4 " CMOS image sensor,2MP
*Maximum resolution up to 1920*1080 (1080P)
*Support two-way intercom, voice prompt.
*ICR infrared filter automatic switching,realize the real day and night monitoring
*Support the standard clear, high-definition resolution to watch,to adapt for variety of network environment
*Support mobile phones real-time monitoring
*Support PTZ control,remote capture,audio and video recording
*Global network coverage,anytime,anywhere smooth Watch
*Support human tracking
*Upgrade APP N_eye3C, with wordwide servers

N_eye 3C Servers Distribution

Russia(3): Moscow, Siberia
Europe(14): Germany, UK, Italy, Ukraine
China(36) (Aliyun+TencentCloud)
North America(13): Canada Los angel/N.Y
South Asia and Middle East(15): Dubai, Iran, Turkey, India
Africa(2): Egypt, South Africa
Southeast Asia(14): Singapore, Indonesia, Thailand
South America (3): Brazil
Australia(1): Sydney

N_eye 3C
The Upgrade APP for MVTEAM WIFI Smart Camera

12 Core Functions

Wifi Smart Cloud IP Camera

HD 720P — 720P HD

two-way intercom

voice prompt

Cloud — P2P Cloud

ICR — ICR filter

5m IR

Motion detection

Wifi

Remote View

64G — SD Card

Plug and Play

Autoalarm

MVTEAM

A variety of installation

Ceilling mount

Wall mount

Flatwise

P/T Rotation

90°
350°

Finger sliding screen to remote control camera rotation

A variety of applications

Baby Care

Elderly Care

Pets Care

Shop monitor

Motion Detction Alarm

Support SD Card

The camera doesn't come with sd card,if you need buy from us,please ask the sales.

microSDHC
10
64GB

max support
64G SD Card

Live view in Daytime

Live view at night

Show appearance

HD lens

loudspeaker

screw hole for fixing camera

microphone

Power port

Reset Button

142.8mm

87.1mm

87.1mm

M'TEAM

Model No.		H100-Q8
Camera	Sensor type	1/4" Progressive Scan CMOS
	Minimum illumination	0.02Lux @(F2.0,AGC ON) ,0 Lux with IR
	shutter	Shutter adaptation
	Camera lens	3.6mm
	Lens interface type	M12
	Day and night conversion mode	ICR infrared filter
	Digital noise reduction	3D digital noise reduction
Compression standard	Video compression standard	H.264
	Coding type	H.264 Main Profile
	Video compression rate	HD, SD, rate adaptation.
	Audio compression standard	AAC
	Audio compression rate	Rate adaptation
Image	Maximum image size	1920 × 1080
	frame rate	Max:25fps network transmission rate: adaptive adjustment
	Image setting	Brightness, contrast, saturation, etc. (through the client to adjust the setting)
Network function	Storage function	Support Micro SD card (max 128G)
	Intelligent alarm	Video is lost, the network is disconnected, and the power is disconnected.
	General functions	Reverse, capture, mobile alarm, password protection, video playback, remote control, two-way intercom
Wireless parameter	Wireless standard	IEEE802.11b, 802.11g, 802.11n Draft
	frequency range	2.4 GHz ~ 2.4835 GHz
	Channel bandwidth	Support 20/40MHz
	security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
	transmission speed	11b: 11Mbps,11g :54Mbps,11n :135Mbps
General specification	temperature and humidity	-10 C ~50 C, the humidity is less than 95% (no condensation)
	Power	DC 5V
	Power consumption	3W MAX
	Infrared radiation distance	MAX 5meter
	Size(mm)	87.1mm x 87.1mm x 142.8mm
	weight	200g(Containing packaging)

CE, ROHS, FCC Certificates

▼ Standard Package

MVTEAM

▼ Advanced Package

MVTEAM

Contact us:

If you have any question, welcome to **Contact us**.
Your close attention to our company is highly appreciated.
Welcome to visit our official website **www.mvteamcctv.com**

Related Articles about Wifi IP Camera:

[How to Set Motion Detection for Wifi IP Camera?](#)
[How Long Video Records Does a TF Card Can Save for Wifi Cameras?](#)
[How to remote view MVTEAM Wifi IP Camera on Computer?](#)