

### Main Features:

- 1.0M/1.3M/2.0M pixel full real time optional, Highest resolution 1080P
- follow HD and CVBS video standard
- 6mm(M12) fixed Lens
- Water Resistant Rate: IP66
- support transmission distance above 500M under general 75- 3 coaxial cable without loss
- High-speed, long-distance, real-time transmission
- support OSD menu
- with ICR switching , to achieve Day and Night monitoring
- Used genuinely imported 3rd generation IR LEDs and megapixel high definition lens, these cameras have been featured as great performance in color restoration, image definition and night viewing.

### Application Places:

Apply to the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

Model	MVT-AH11A	MVT-AH11B
Sensor	1/4 "CMOS Pixelplus 1.0M / 720P + OV9712 NVP2431H	1/3 "CMOS Pixelplus 1.3M / 1024P + NXP2430H SONY238
SIGNAL	PAL / NTSC	PAL / NTSC
Video Output	HD- <b>AHD</b> / CVBS	HD- <b>AHD</b> / CVBS
Effective Pixels	1280 (H) * 720 (V)	1280 (H) * 1024 (V)
Min. Lighting	0.05Lux @ color, 0.01Lux B / W	0.05Lux @ color, 0.01Lux B / W
Shutter	4 / 25s ~ 1 / 45,000s	4 / 25s ~ 1 / 45,000s
Frequency of the video	1280 × 720 @ 50 fps; 1280 × 720 @ 60 fps	1280 × 1024 @ 50 fps; 1280 × 1024 @ 60 fps
Synchronization	Internal	Internal

Video Output	High definition video output BNC HDAHD / 1 channel CVBS	High definition video output BNC HDAHD / 1 channel CVBS
BLC	optional	optional
OSD	optional	optional
AWB	Automatic / manual / Day / Night	Automatic / manual / Day / Night
Day Night	Auto (ICR) / Color / B / W	Auto (ICR) / Color / B / W
Transmission Distance	Over 500m via coaxial cable 75-3	Over 500m via coaxial cable 75-3
Power supply	DC 12V $\pm$ 10%	DC 12V $\pm$ 10%
Working environment	30 ° C to + 60 ° C / 95% RH less (no condensation)	30 ° C to + 60 ° C / 95% RH less (no condensation)
Energy consumption	4W MAX	4W MAX

## ● PRODUCT PICTURE

**M'TEAM**



## ● FACTORY & OFFICE

M' TEAM



## ● EXHIBITIONS

M' TEAM

