

Main Features:

- 1.0M/1.3M/2.0M pixel full real time optional,Highest resolution 1080P
- follow HD and CVBS video standard
- with 6-22mm(M12) vari-focal Lens
- Water Resistant Rate:IP66
- support transmission distance above 500M under general 75- 3 coaxial cable without loss
- High-speed, long-distance, real-time transmission
- support OSD menu
- with ICR switching , to achieve Day and Night monitoring
- Used genuinely imported 3rd generation IR LEDs and megapixel high definition lens, these cameras have been featured as great performance in color restoration,image definition and night viewing.

Model		AHD- AH58
Compression		H.264 Standard compression
Operation		Embedded Linux
Image coding-control		Image edit adjustable,both changable and fix stream optional
Dual stream		Can be set up in each channel
Monitor image quality		16*720P(AHD), 16*960H(Analog DVR)
Image dynamic detection		Multiple detection areas in each channel
Video framerate		720P 25FPS/CH AHD,960H 25FPS/CH Analog DVR
Image playback quality		AHD 720P 100FPS ,Analog DVR 16*960H 100FPS
Video mode		Support manual, automatic, dynamic monitoring, alarm trigger video mode
Backup mode		U disk, USB portable disk, USB burn, Network storage and backup
Operate mode		Mouse, Remote controller,Front Panel Control
login locally		admin and password
Save recording		local hard disk and network
External interface	Video input	720P 25FPS/CH AHD,960H 25FPS/CH Analog DVR
	Audio input	1×RCA
	Video output	1*VGA,1*HDMI
	Audio output	1*RCA,1*HDMI
	Network interface	10M/100M base-T Ethernet (RJ-45)
	USB connect port	2 x USB 2.0
	RS485	RS485*1
	Alarm input	NO
	Alarm output	NO
Hard disk	Internal HDD	1 SATA HDD port
	Maximum capacity	Maximum 4TB each SATA□
Cell phone monitoring		Support Window Mobile, iPhone,iPad, Android
Power		12V/2A
DVR size		240(L)*260(w)x60(H)mm
Weight		2.0kg(W/O HDD)

● PRODUCT PICTURE

M TEAM



● FACTORY & OFFICE

M TEAM



