

Câmera Ethernet H.265 de monitoramento de vídeo 4MP (MVT-M2892)

● FEATURES



- Adota Sensor CMOS de Scanning Progressivo de 4.0Megapixel com baixa iluminação.
- Suporta Vídeo em Rede do H.264 HP H.265 4MP @15fps, 3MP @25Resolução de fps.
- **Vandal completo**Proof Dome (caixa de metal)
- Built-in: lente métrica de 6 mm de megapixel de 3mmPOE e DC12V, entrada / saída de áudio, Visão noturna 30 metros.
- RTSP padrão e FLASH Vídeo suportado, suporte Internet Explorer, Firefox, Safari, Chrome, Opera etc.
- Suporte duas vias falando entre câmera com PC remoto ou celular através da Internet.
- Android e IOS P2P Free App, Free CMS.
- Personalizada Versão completa da ONVIF com boa competitividade com o Main Stream 3rd CMS e NVRs

● SPECS



Full HD, em rede

- DSP de alto desempenho usando código de compressão de vídeo H.265.
- Algoritmo de codificação inteligente otimizado para um vídeo mais claro com menor largura de banda.

Qualidade Confiável

- Full Metal Shell, design de precisão, design de invólucro à prova de vandalismo.
- Lighting Prottech com 6Kv, eletrostática de 8Kv com proteção de entrada de energia.

Funcionalidade Completa

- Design de alojamento de cúpula, é bom manter Consistente e fácil para a instalação de teto e parede DIY.
- Vigilância mista de áudio e vídeo suportada.
- Built-in IEEE802.3af POE.

Features		POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access
Cameras	Solution	Hi3516D+OV4689
	Sensor	1/3" CMOS
	Min. Illumination (Color)	0.01Lux/F1.2
	Shutter	1/5s-1/50,000s
	Day&Night	IR-CUT Auto, Black, Color
	Images Settings	Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise
Codec	Video Resolution	4.0M(2592*1520)@15FPS, 3M@25FPS
	Codec	H.265
	Video Frames	Real Time, Max 25fps
	Codec Mode	VBR/CBR
	Data Rate	Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps
	Frames	1-30 frame adjustable
	Record	Video and Audio Recording and Playback, MP4 Format
Network	Internet	QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS
	Network Video	Standard RTSP, FLASH
	Remote Access	QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS
	Compatibility	Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs
	WIFI	NO
	POE	Inside, IEEE802.3af
	Network Protocol	P2P, RTP, RTSP, TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP
Advanced	System	Time Sync. (Auto/Mannual/NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports
	Audio&Video	Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection
	Storage	NVR, Cloud
	Events/Security/Log	Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Acceess etc.)
Hardware	Network Interfaces	RJ-45, 10/100Base-T
	Microphone	NO
	Audio via Cable	Audio In/Out, Talkback (G.711A, G.711U)
	Local Storage	NO
	Others	NO
	Application	Indoor and Outdoor
	Installation	Wall-mounting, Ceiling-mounting
	Accessories	CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual.
		Others: Printed Quick-Start, Installation Location Lable, Installation Kits .
	Power Supply	DC12V & POE
	Work Temperature	-10°C-50°C
	Work Humidity	10%-90%
	Power Consumption	2 Watt

● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

